



QINGDAO POLYFUSION MACHINERY CO.,LTD.

RM102, Entrance 3 Building 4,Jiazhaoyeshuianxindu,No.358,Wangsha Road,Chengyang

District,Qingdao,Shandong Tel.: 0086-532-66733884 Mobile: +86 15763934591 Daisy

www.qdpolyfusion.com E-mail: export04@qdpolyfusion.com

FICHA TÉCNICA



Modelo	PFE315B	PFE400B	PFE500B	PFE600B	PFE1000B
Gama de soldadura	20-315mm	20-400mm	20-500mm	20-630mm	20-1000mm
Voltaje de entrada	Ac220±20% 40-65Hz		Ac380±20% 40-65Hz		
Potencia nominal	3.5KW	4.0KW	8.0KW	12.0KW	15.0KW
Corriente nominal	60A	75A	70A	80A	80A
Tensión nominal	70V	60V	150V	180V	210V
Cantidades de registro de datos	500	1000	500		
Puerto de salida de datos	USB Port & Scanner				
Dimensión del paquete	520X310X400mm	560X280X430mm	540X340X440mm	540x340x440mm	650X440X520mm
Peso	13.0Kg	13.1Kg	15.0Kg	26.0Kg	30.0Kg



QINGDAO POLYFUSION MACHINERY CO.,LTD.

RM102, Entrance 3 Building 4,Jiazhesoyeshuianxindu,No.358,Wangsha Road,Chengyang

District,Qingdao,Shandong Tel.: 0086-532-66733884 Mobile: +86 15763934591 Daisy

www.qdpolyfusion.com E-mail: export04@qdpolyfusion.com
